

KEY:	
500 SERIES - DRAINAGE	
	- Proposed new gully.
	- Proposed ACO drain or similar approved.
	- Proposed fluted drainage channel.
	- Proposed ACO drain or similar approved.
	- Proposed fluted drainage channel.
	- Proposed ACO drain or similar approved.
	- Proposed fluted drainage channel.
	- Proposed ACO drain or similar approved.
	- Proposed fluted drainage channel.
	- Proposed ACO drain or similar approved.
	- Proposed fluted drainage channel.
	- Proposed ACO drain or similar approved.
	- Proposed fluted drainage channel.
	- Proposed ACO drain or similar approved.
	- Proposed fluted drainage channel.
	- Proposed ACO drain or similar approved.
	- Proposed fluted drainage channel.
	- Proposed ACO drain or similar approved.
	- Proposed fluted drainage channel.
	- Proposed ACO drain or similar approved.
	- Proposed fluted drainage channel.
	- Proposed ACO drain or similar approved.
	- Proposed fluted drainage channel.
	- Proposed ACO drain or similar approved.
	- Proposed fluted drainage channel.
	- Proposed ACO drain or similar approved.
	- Proposed fluted drainage channel.
	- Proposed ACO drain or similar approved.
	- Proposed fluted drainage channel.
	- Proposed ACO drain or similar approved.
	- Proposed fluted drainage channel.
	- Proposed ACO drain or similar approved.
	- Proposed fluted drainage channel.
	- Proposed ACO drain or similar approved.
	- Proposed fluted drainage channel.
	- Proposed ACO drain or similar approved.

700 SERIES - PAVEMENTS	
	Area to receive carriageway construction and benching (see cross section for detail). Area = 117.0m²
	Area to be milled 40-100mm and receive 40mm Surface Course (see cross section for detail). Area = 3266.0m²
	Area to receive red coloured high friction surface. Area = 89.0m²

1100 SERIES - KERBS, FOOTWAYS AND PAVED AREAS	
	FOOTWAY CONSTRUCTION: • 20mm thick dense asphalt concrete surface course with 6mm nominal aggregate (exclude gravel. Minimum PS) • 50mm thick dense binder concrete with 20mm nominal aggregate • 100mm - 200mm Type 1 granular Sub-base • Gextilex Area = 1034.0m²
	Tactile paving area (brise profile/buff coloured) Area = 50.0m²
	Tactile paving area (cordury profile/buff coloured) Area = 15.0m²

1200 SERIES - TRAFFIC SIGNS AND ROAD MARKINGS

BOLLARDS

B2 Non-illuminated bollard - Impactapol material
Black coloured bollard Red/White retroreflective bands.
Total No. = 6

B1 Sign-carrying bollard with Shared use sign on one aspect (Glasdon Ensign)

 SU - Shared Use
ER - End of Route

Total No. = 2

[illegible]